

## Specifications

Transaxle type		M6CF3-1	
Engine type		Diesel 1.6 (General Countries)	Diesel 1.6 (Central and Southern America)
Gear ratio	1st	3.636	3.769
	2nd	1.962	2.040
	3rd	1.189	1.189
	4th	0.844	0.844
	5th	0.702	0.702
	6th	0.596	0.596
	Reverse	3.583	3.583
Final gear ratio		3.706	3.941

## Tightening Torques

Items	N.m	kgf.m	lb-ft
Oil drain plug	58.9 ~ 78.5	6.0 ~ 8.0	43.4 ~ 57.8
Oil filler plug	58.9 ~ 78.5	6.0 ~ 8.0	43.4 ~ 57.8
Shift lever assembly bolt	8.8 ~ 13.7	0.9 ~ 1.4	6.5 ~ 10.1
Back up lamp switch	29.4 ~ 34.3	3.0 ~ 3.5	21.7 ~ 25.3
Transaxle support bracket bolt	88.3 ~ 107.9	9.0 ~ 11.0	65.1 ~ 79.6
Start motor installation bolt	38.2 ~ 58.8	3.9 ~ 6.0	28.2 ~ 43.4
Roll rod bracket bolt	(A) 49.0 ~ 63.7	5.0 ~ 6.5	36.2 ~ 47.0
	(B) 107.9 ~ 127.5	11.0 ~ 13.0	79.6 ~ 94.1
Transaxle upper mounting bolt (TM=>ENG)	58.9 ~ 78.5	6.0 ~ 8.0	43.4 ~ 57.8
Transaxle lower mounting bolt (ENG=>TM)	(A) 34.3 ~ 49.1	3.5 ~ 5.0	25.3 ~ 36.2
	(B) 42.2 ~ 53.9	4.3 ~ 5.5	31.1 ~ 39.8

## Lubricants

Items	Recommend lubricant	Quantity
Transaxle gear oil	SAE 75W/85 API GL-4 TGO-7(MS517-14)	1.9L (0.50 U.S.gal., 2.0 U.S. qt., 1.67 Imp qt.)
Air breather	MS721-38	As required
Transaxle housing	MS721-40 or MS721-38	As required (Ø1.0 ~ Ø1.5 mm)
Surface of release fork and bearing	Grease (CASMOLY L9508)	As required

